




114.4279

Assembly Gloves

Suitable for:

Full nitrile microfoam coating, unlined

mechanics when handling hot parts



- High durability, dexterity and tactile sensitivity.
- Resistant to contact heat up to 100°C for 15 s.
- Water and oil repellent.
- Sanitized® treated to prevent bacteria growth and promote freshness.

Light and medium fabrication | General assembly | Automotive manufacturing | Motor

Standards and **Approvals**



EN 420:2003 + A1:2009















Oil repellent

Water repellent

INDUSTRY:

Agriculture

Building and Construction

Logistics and Warehousing

Maintenance

Oil, Gas and Mining

STANDARDS AND APPROVALS:

EN 420:2003 + A1:2009

EN 388:2016

EN 407:2004

CE Cat.II

PROTECTION AND **RESISTANCE:**

Abrasion resistant

Oil repellent

Water repellent

FEATURES AND PROPERTIES:

Precision

Seamless

PRODUCT DETAILS

| Liner material : | Nylon |
|--------------------|--------------|
| Coating material : | Nitrile |
| Coating type : | Fully coated |
| Grip: | Dry |
| Glove fit : | Tight fit |

| Size : | 7 8 9 10 11 12 |
|---------|--------------------------|
| Length: | 23-26 cm |
| Color: | Black |

PACKING / TRANSPORT

Sales Units Per Bundle: 12

Sales Units Per Outer Case: 144